



COVID-19 Update: Zip Water is open for business. Find out what steps we are taking to safeguard your health and continue to serve you. [Covid19 Update](#) ×

ZIP HYDROTAP CS



CHILLED



SPARKLING

FILTERED

Order Code HT1787Z1

Zip HydroTap Chilled, Sparkling, Filtered water appliance featuring a single under bench command centre including full colour interactive touch screen display with pin code protection, 0.2 micron water filtration and 2 disposable CO2 cylinders.



Manufacturing Code 0054AU1S2ZN1R

Capacity Residential

Disability Options Unavailable

Tap	Zip HydroTap CLASSIC Tap (Brushed Chrome)
Water Pressure	Min 250kPa - Max 700kPa
Water Connection	12.7mm BSP
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	0.35kW 220-240V 50Hz
Power Supply	1 x 10Amp GPO
Dimensions	H333mm x W280mm x D405mm
Product Approvals	WaterMark, CE, RCM, ARC

Warranty

5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail



