



HYDROTAP G5 BC20 CLASSIC PLUS CHROME



BOILING

CHILLED

FILTERED

Order Code H55702Z00AU

Zip HydroTap Classic Plus Boiling, Chilled, Filtered water features simple, intuitive controls including continuous flow to fill bottles, Boiling water safety lock, and SteriTouch® antimicrobial protection impregnated within the new Classic Plus touch-pad for enhanced hygiene. The water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.



Manufacturing Code	H55702Z00AU
--------------------	-------------

Capacity	Commercial
----------	------------

Boiling Cups per hour	100
-----------------------	-----

Chilled Cups per hour	75
-----------------------	----

Tap	Zip HydroTap CLASSIC PLUS Tap (Chrome)
-----	--

Water Pressure	Min 170kPa - Max 700kPa
----------------	-------------------------

Water Connection	1/2" BSP (G1/2)
------------------	-----------------

Water Supply Requirements	Cold
---------------------------	------

Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
--------------	--

Power Rating	1.9kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet
Dimensions	W280mm x D455mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com'

Installation Detail

Ventilation requirements Contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

HydroTap Tap options

Classic Plus (216mm high, 116mm wide, 126mm depth)
 Classic (208mm high, 116mm wide, 126mm depth)
 Elite Plus (221mm high, 112mm wide, 134mm depth)
 Touch-Free Wave (214mm high, 116mm wide, 126mm depth)

Font options

Raised Font with 135mm Extension part no. 95258
 (280mm high, 116mm wide, 351mm depth, 268mm base width)

Font with 135mm Extension part no. 90915
 (200mm high, 116mm wide, 351mm depth, 104mm base width)

Tap Positioning
 Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).
 35mm hole for HydroTap Tap

Cutting detail
 Raised Font: 116mm diameter hole for bowl, 35mm hole for tap, 164mm diameter hole for M6 stud.
 Font: 108mm diameter hole for bowl, 35mm hole for tap, 219mm diameter hole for M6 stud.

Installation Diagrams
 Shows the tap and command centre installed in a cabinet. Labels include: Classic Plus Tap, Clearance Envelope, Mains cold water isolation valve (not supplied), IEC Flex & Plug 230-240V, 50Hz power outlet, Air inlet grille, and 4mm buffer pad air space.

HydroTap G5 BC20
 shown with "Classic Plus" Tap

SCALE 1:5
 ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

